

# FLUSH & MOLDED DOORS

REEB® IN-STOCK FLUSH & MOLDED CATALOG





# MILLWORK SHOWROOMS

OUR SHOWROOM, YOUR SHOWROOM



EMERSON, NJ



MIDLAND PARK, NJ



SUCCASUNNA, NJ

Our Millwork Showrooms were built to be an extension of our builder, remodeler, architect and designer customers' business. Featuring inspirational, lifestyle installations, our Showrooms are the ideal location to meet with clients in advance of a project where a number of major decisions can be made. Various moulding options are installed around windows and doors allowing your clients to see, touch and feel the products before they are installed, putting their mind at ease and simplifying the selection process. Complimentary moulding samples are available for jobsite consultations.

TAKE A TOUR AT [KUIKENBROTHERS.COM/SHOWROOMS](http://KUIKENBROTHERS.COM/SHOWROOMS)



**KUIKEN BROTHERS COMPANY INC.**  
RESIDENTIAL & COMMERCIAL BUILDING MATERIALS *Since 1912*

**FAIR LAWN, NJ**  
6-02 Fair Lawn Avenue  
P: (201) 796-2082

**WANTAGE, NJ**  
175 Route 23  
P: (973) 875-5106

**SUCCASUNNA, NJ**  
31 Route 10 East  
P: (973) 968-7700

**EMERSON, NJ**  
246 Kinderkamack Road  
P: (201) 262-6666

**WARWICK, NY**  
33 South Street  
P: (845) 986-2255

**ROSELAND, NJ**  
14 Eisenhower Parkway  
P: (973) 226-5700

**MIDLAND PARK, NJ**  
145 Lake Avenue  
P: (201) 652-1000

**GARFIELD, NJ**  
485 River Drive  
P: (973) 772-0044

## Simple & Cost Effective

Reeb® offers a wide variety of molded doors designed to replicate the look and feel of a traditional wood door at an affordable price.

With layout options from modern and minimalist to classic and conventional, molded interior doors are a popular option in both residential and light-commercial applications.



# Door Styles




## Molded Doors

Molded doors are constructed when a series of panels or design is stamped by a mold into a hardboard fiber material to create the door face. They are manufactured to resemble the look of an interior stile and rail wood door. Solid Particle Core molded doors are available in a variety of designs and can replicate the heavy weight and feel of a real wood door while providing the benefit of noise reduction for a peaceful environment.



### Finishing

Molded doors are available in smooth or textured surfaces. They arrive primed and ready for painting after a light sanding and minor preparation. Because of the materials used in their construction, staining is not an option. Always make sure to finish all six sides.



## Flush Doors

Flush doors are constructed using a mixture of wood and wood-fiber components and feature a completely flat surface for a simple and economical design option. They are available in a variety of wood species, most of which can be painted or stained. Some flush doors also come in a primed hardboard or woodgrained pre-finished option.

### Finishing

Flush doors are available in paint-grade, stain-grade and primed hardboard options. Primed flush doors require only a light sanding and cleaning before applying a base coat.



### Stain-Grade:

Birch and Oak doors feature solid wood edges and all the pleasing color variations and grain patterns found in a natural wood product. They look great painted or stained.



### Paint-Grade:

Lauan doors typically feature irregular colors and grain patterns that most homeowners will opt to paint over. Flush hardboard doors are factory primed and ready for painting.

# Door Applications




## Bi-Fold Doors

Bi-Fold doors are a popular option for saving room in closet areas or other tight spaces throughout your home. These doors provide better access to small areas and take up minimal space. All Reeb® molded bi-fold doors feature panels on both sides.

---

## Sliding Bypass Doors

Sliding Bypass doors are configured by hanging two or more interior doors mounted to a track. They do not swing and are typically useful in areas with little available floor space.



## Pocket Doors

Pocket doors slide similarly to a bypass door, but are generally a single door mounted to an overhead track that slides into the wall, hiding the components and saving space.

## Mirror Doors

Whether it's a bathroom, bedroom, narrow hallway or gym, mirror doors enhance ambient light and create the effect of a larger space.




## Custom Sized Doors

For odd sized openings, doors can be crafted from standard flush and molded components, for example, attic access and under the stairs storage. Flush doors can be reduced to any height to fit your requirements. Depending on the specific design, some molded doors can also be reduced to fit custom applications.

## Barn Door Hardware

Barn Door Hardware allows the door to slide horizontally beyond the opening on a track mounted above the door. This allows you to make the most of your available living space while adding a rustic, yet elegant look.

**See page 45** for more information on Barn Door Hardware.



# Slab or Door Unit

**Single Door**  
(No Frame)

**Pre-Hung Unit**  
(Fully Assembled)

Doors can be purchased as a single door only (no frame) or fully assembled pre-hung units.


In a pre-hung unit, the door comes mounted in a frame with hinges already attached to a door jamb. Reeb® stocks several paint-grade and stain-grade jamb options to complement the door.

**See page 42** to learn more.

Reeb stocks interior doors with the option of either "full and square" or pre-fit and beveled edges.


## Pre-fit and Beveled Edges

Typically used on pre-hung door units, edges are undersized by 3/16" and feature a 3 degree bevel on both sides, eliminating the need to field-trim the door to fit the frame.



## Full and Square Edges

Typically used for replacements, these doors feature a 90 degree angle on all edges, allowing the door to be field-trimmed if necessary.



# Construction Types

## Solid Particle Core (SC)

- Weight and feel of a wood door
- Reduces sound transmission
- Reeb® stocks Solid Particle Core doors with a triple-bottom rail and wood stiles and rails for additional screw holding power
- Great for residential and light-commercial applications like living rooms, bedrooms, hallways and large storage areas
- Can be fire-rated up to 20 minutes with certified frames and hardware

**See pages 8-9** for more information on Solid Particle Core construction.



## Hollow Core (HC)

- Standard offering includes wood stiles for added screw holding power and easy size reductions
- Also available with MDF/Fiber stiles
- Commonly used in residential applications where sound transmission and durability is not a primary concern

**See pages 10-11** for more information on Hollow Core construction.



## Solid Mineral Core (MC)

- Weight and feel of a wood door
- Reduces sound transmission
- Manufactured with a special fire-resistant core and Firestop material allowing a fire rating of up to 60 minutes with certified frames and hardware
- Commonly used in applications that require up to a 60-minute fire rating like house-to-garage entryways and light-commercial buildings

**See pages 12-13** for more information on Solid Mineral Core construction.

**See pages 43-44** for more information on hardware and accessories required by fire safety laws and regulations.



# Solid Particle Core (SC)

Construction

1. **Wood Stiles & Rails:** Made of solid wood for extra screw holding power
2. **Face:** 1/8" molded hardboard skin available in smooth or textured painting surface
3. **Core:** Solid particle board core routed to match molded skin design
4. **Thickness:** Available in 1-3/8" & 1-3/4"
5. **Height:** Available in 6/8, 7/0 & 8/0



## A Wood Rail

Triple-bottom wood rail for added durability and ease of trimming (Note: Field-trimming can affect fire ratings. To ensure proper ratings, doors must be factory trimmed by Reeb®)

### Rail (6/8 height, 1-3/8" thickness doors):

1" (single) top rail and 3" (triple) bottom rail, allowing the door to be field-trimmed up to 2"

### Rail (6/8 height, 1-3/4" thickness doors):

1" (single) top rail and 2" (double) bottom rail, allowing the door to be field-trimmed up to 1"

**Rail (7/0 & 8/0 height):** All doors in 7/0 and 8/0 height have a single 1" top rail and a 2" bottom rail allowing the door to be field-trimmed up to 1"



**Fire Rating**  
UP TO 20 MINUTES



**Sound Benefits**  
REDUCED SOUND  
TRANSMISSION


Solid Particle Core molded doors are used in a variety of residential and light-commercial interior applications. The advantages of solid particle core construction are added security and reduced sound transmission while the heavier weight and feel is similar to a wood stile and rail door. Reeb® offers a wide variety of designs with smooth or textured surfaces.



#### Panel Options




Raised Panel



Flat Panel

#### Surface Options



Smooth Surface



Textured Surface


#### Sticking Options



Craftsman Sticking



Cove & Bead Sticking



Ovolo Sticking



Step Sticking

# Hollow Core (HC)

## Construction

1. **Wood Stile (Left Side):** Wood stiles for additional screw holding power
2. **Fiber Stile (Right Side):** Medium density fiberboard (MDF) stiles
3. **Blocking:** Provides support for door faces
4. **Face:** 1/8" molded hardboard skin available in smooth or textured painting surface
5. **Core:** Hollow core routed to match molded skin design
6. **Thickness:** Available in 1-3/8" Only
7. **Wood Stile Height (Left Side):** Available in 6/8, 7/0 & 8/0
8. **Fiber Stile Height (Right Side):** Available in 6/8 Only



## A Wood Stile Hollow Core Door


**Rail (6/8 height, 1-3/8" thickness doors):** 1" (single) fiber top rail and 3" (triple) fiber bottom rail, allowing the door to be field-trimmed up to 2"

**Rail (7/0 & 8/0 height, 1-3/8" thickness doors):** 1" fiber top rail and a 2" fiber bottom rail, allowing the door to be field-trimmed up to 1"

## B Fiber Stile Hollow Core Door

**Rail: (6/8 Height, 1-3/8" thickness doors):** Single fiber top and bottom rail. Cannot be field-trimmed without reblocking. If trimming is required, please consider purchasing doors with wood stiles.


Hollow Core molded doors offer a lighter-weight, economic alternative to wood stile and rail interior doors. Available in a variety of designs with smooth or textured surfaces.



#### Panel Options




Raised Panel



Flat Panel

#### Surface Options



Smooth Surface



Textured Surface

#### Sticking Options



Craftsman Sticking



Cove & Bead Sticking



Ovolo Sticking



Step Sticking

# Solid Mineral Core (MC)

Construction

1. **Stile:** Firestop with softwood edges
2. **Face:** 1/8" molded hardboard skin available in smooth or textured painting surface
3. **Core:** Solid Mineral Core manufactured for up to 60 minute fire label requirements, routed to accept molded skins
4. **Thickness:** Available in 1-3/4" only
5. **Height:** Available in 6/8 & 7/0



## A Firestop Stiles & Rails

**Stile (6/8 & 7/0 height, 1-3/4" thickness doors):**  
1/4" softwood edge and 1" Firestop stile

**Rail (6/8 & 7/0 height, 1-3/4" thickness doors):**  
2" Firestop top and bottom rail




**Fire Rating**  
UP TO 60 MINUTES



**Sound Benefits**  
REDUCED SOUND  
TRANSMISSION

Solid Mineral Core molded doors are a popular choice for up to 60 minute fire-rated applications. They are constructed from fire-rated mineral core material and protected by Firestop stiles and rails. Available in a variety of designs with smooth or textured surfaces.




#### Panel Options



Raised Panel

#### Surface Options



Smooth Surface




Textured Surface

#### Sticking Options



Cove & Bead Sticking



Ovolo Sticking




Select a layout that complements the interior design of your home.

Choose from 18 traditional molded designs available in a smooth or textured surface.


**See pages 15-17** for more information.






MOLDED DOORS	Madison	Monroe	Cambridge	Corvado	Continental	Santa Fe
LAYOUT	1 Panel	2 Panel	2 Panel	2 Panel	2 Panel	2 Panel
PANEL TYPE	Flat Panel	Flat Panel	Raised Panel	U-Groove Plank	Raised Panel	V-Groove Plank
SURFACE	Smooth	Smooth	Smooth	Smooth	Smooth	Smooth
STICKING	Craftsman	Craftsman	Ovolo	Cove & Bead	Ovolo	Ovolo
<i>Solid Particle Core</i>						
HEIGHT	6/8, 7/0, 8/0	6/8, 8/0	6/8, 7/0, 8/0	6/8, 8/0	6/8, 7/0, 8/0	6/8, 7/0, 8/0
THICKNESS	1-3/8" & 1-3/4"	1-3/8"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"
FIRE RATING	20 Minute	20 Minute	20 Minute	20 Minute	20 Minute	20 Minute
<i>Hollow Core</i>						
HEIGHT	6/8	6/8, 8/0	6/8, 7/0, 8/0	6/8, 8/0	6/8, 7/0, 8/0	6/8, 7/0, 8/0
THICKNESS	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"
FIRE RATING	None	None	None	None	None	None
<i>Solid Mineral Core</i>						
HEIGHT	N/A	N/A	6/8, 7/0	N/A	6/8, 7/0	N/A
THICKNESS	N/A	N/A	1-3/4"	N/A	1-3/4"	N/A
FIRE RATING	N/A	N/A	60 Minute	N/A	60 Minute	N/A
PAGE	page 18	page 19	page 20	page 21	page 22	page 23

# Layouts



MOLDED DOORS	Princeton	Camden	Craftsman III	Avalon	Coventry	Provincial
LAYOUT	2 Panel	2 Panel	3 Panel	3 Panel	4 Panel	4 Panel
PANEL TYPE	Raised Panel	Raised Panel	Flat Panel	Raised Panel	Raised Panel	Raised Panel
SURFACE	Smooth	Textured	Smooth	Textured	Smooth	Textured
STICKING	Cove & Bead	Cove & Bead	Craftsman	Cove & Bead	Cove & Bead	Ovolo
Solid Particle Core						
HEIGHT	6/8, 7/0, 8/0	6/8	6/8, 7/0	6/8	6/8, 7/0, 8/0	6/8
THICKNESS	1-3/8" & 1-3/4"*	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"
FIRE RATING	20 Minute	20 Minute	20 Minute	20 Minute	20 Minute	20 Minute
Hollow Core						
HEIGHT	6/8, 7/0, 8/0	6/8	6/8, 7/0	6/8	6/8	6/8
THICKNESS	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"
FIRE RATING	None	None	None	None	None	None
Solid Mineral Core						
HEIGHT	6/8	N/A	N/A	N/A	6/8, 7/0	N/A
THICKNESS	1-3/4"	N/A	N/A	N/A	1-3/4"	N/A
FIRE RATING	60 Minute	N/A	N/A	N/A	60 Minute	N/A
PAGE	page 24	page 25	page 26	page 27	page 28	page 29

\* 1-3/4" Available in 6/8 & 8/0 Only




MOLDED DOORS	Rockport	Conmore	Colonial	Colonist Smooth	Colonist Textured	Mirror
LAYOUT	5 Panel	5 Panel	6 Panel	6 Panel	6 Panel	
PANEL TYPE	Raised Panel	Flat Panel	Raised Panel	Raised Panel	Raised Panel	Beveled Glass
SURFACE	Smooth	Smooth	Textured	Smooth	Textured	Textured
STICKING	Cove & Bead	Step	Ovolo	Cove & Bead	Cove & Bead	Ovolo
Solid Particle Core						
HEIGHT	6/8, 7/0, 8/0	6/8, 7/0	6/8	6/8, 7/0, 8/0	6/8, 7/0	N/A
THICKNESS	1-3/8" & 1-3/4"	1-3/8" & 1-3/4" <sup>†</sup>	1-3/8" & 1-3/4"	1-3/8" & 1-3/4"	1-3/8" & 1-3/4" <sup>†</sup>	N/A
FIRE RATING	20 Minute	20 Minute	20 Minute	20 Minute	20 Minute	N/A
Hollow Core						
HEIGHT	6/8, 7/0, 8/0	6/8, 7/0	6/8	6/8, 7/0, 8/0	6/8, 7/0, 8/0	6/8
THICKNESS	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"
FIRE RATING	None	None	None	None	None	None
Solid Mineral Core						
HEIGHT	N/A	N/A	N/A	6/8, 7/0	6/8	N/A
THICKNESS	N/A	N/A	N/A	1-3/4"	1-3/4"	N/A
FIRE RATING	N/A	N/A	N/A	60 Minute	60 Minute	N/A
PAGE	page 30	page 31	page 32	page 33	page 34	page 35


<sup>†</sup> 1-3/4 Available in 6/8 Only

# Madison

LAYOUT OPTIONS




STANDARD



TALL




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC	SC	SC		SC	
	1/8	SC/HC		SC			
	1/10	SC/HC					
	2/0	SC/HC	SC	SC	SC	SC	
	2/2	SC/HC					
	2/4	SC/HC	SC	SC	SC	SC	
	2/6	SC/HC	SC	SC	SC	SC	SC
	2/8	SC/HC	SC	SC	SC	SC	SC
	2/10	SC/HC	SC	SC	SC	SC	
	3/0	SC/HC	SC	SC	SC	SC	SC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	
2/6	SC/HC
2/8	
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	
5/0	SC/HC
5/4	
6/0	SC/HC



Smooth Surface



Craftsman Sticking


# Monroe

LAYOUT OPTIONS




		STANDARD				TALL	
HEIGHT		6/8		7/0 - N/A		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0						
	1/2						
	1/3						
	1/4						
	1/6	SC/HC				SC/HC	
	1/8						
	1/10						
	2/0	SC/HC				SC/HC	
	2/2						
	2/4	SC/HC				SC/HC	
	2/6	SC/HC				SC/HC	
	2/8	SC/HC				SC/HC	
	2/10						
	3/0	SC/HC				SC/HC	

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	
2/6	SC/HC
2/8	
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	
5/0	SC/HC
5/4	
6/0	SC/HC



Smooth Surface



Craftsman Sticking

SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 MC = Solid Mineral Core Construction  
 ☒ = No Standard Bore Possible

# Cambridge

LAYOUT OPTIONS



STANDARD



TALL




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC		SC/HC		SC/HC	
	1/2	SC/HC		SC/HC		SC/HC	
	1/3	SC/HC		SC/HC		SC/HC	
	1/4	SC/HC		SC/HC		SC/HC	
	1/6	SC/HC	SC	SC/HC	SC	SC/HC	SC
	1/8	SC/HC		SC/HC		SC/HC	
	1/10	SC/HC		SC/HC		SC/HC	
	2/0	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/2	SC/HC		SC/HC		SC/HC	
	2/4	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/6	SC/HC	SC/MC	SC/HC	SC	SC/HC	SC
	2/8	SC/HC	SC/MC	SC/HC	SC/MC	SC/HC	SC
	2/10	SC/HC	SC	SC/HC	SC	SC/HC	SC
	3/0	SC/HC	SC/MC	SC/HC	SC/MC	SC/HC	SC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Smooth Surface



Ovolo Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:

1/6, 2/0, 2/4, 2/6, 2/8, 2/10, 3/0

# Corvado

LAYOUT OPTIONS



STANDARD



TALL




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0 - N/A		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC				SC/HC	
	1/8	SC/HC					
	1/10	SC/HC					
	2/0	SC/HC				SC/HC	
	2/2	SC/HC					
	2/4	SC/HC				SC/HC	
	2/6	SC/HC	SC			SC/HC	
	2/8	SC/HC	SC			SC/HC	
	2/10	SC/HC					
	3/0	SC/HC	SC			SC/HC	

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	
2/6	SC/HC
2/8	
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	
5/0	SC/HC
5/4	
6/0	SC/HC



Smooth Surface



Cove & Bead Sticking



U-Groove Plank


SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 MC = Solid Mineral Core Construction  
 ☒ = No Standard Bore Possible

# Continental

LAYOUT OPTIONS



STANDARD



TALL




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC		SC/HC			
	1/2	SC/HC		SC/HC			
	1/3	SC/HC		SC/HC			
	1/4	SC/HC		SC/HC			
	1/6	SC/HC	SC	SC/HC	SC	SC/HC	SC
	1/8	SC/HC		SC/HC		SC/HC	
	1/10	SC/HC		SC/HC		SC/HC	
	2/0	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/2	SC/HC		SC/HC		SC/HC	
	2/4	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/6	SC/HC	SC/MC	SC/HC	SC	SC/HC	SC
	2/8	SC/HC	SC/MC	SC/HC	SC/MC	SC/HC	SC
	2/10	SC/HC	SC	SC/HC	SC	SC/HC	SC
	3/0	SC/HC	SC/MC	SC/HC	SC/MC	SC/HC	SC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Smooth Surface



Ovolo Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:

1/6, 2/0, 2/4, 2/6, 2/8, 2/10, 3/0

# Santa Fe

LAYOUT OPTIONS



STANDARD



TALL




BI-FOLD




Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC	SC	SC/HC		SC/HC	
	1/8	SC/HC		SC/HC		SC/HC	
	1/10	SC/HC					
	2/0	SC/HC	SC	SC/HC		SC/HC	
	2/2	SC/HC					
	2/4	SC/HC	SC	SC/HC		SC/HC	
	2/6	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/8	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/10	SC/HC	SC				
	3/0	SC/HC	SC	SC/HC	SC	SC/HC	SC


6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Smooth Surface



Ovolo Sticking



V-Groove Plank

SC = Solid Particle Core Construction  
HC = Hollow Core Construction  
MC = Solid Mineral Core Construction  
⊗ = No Standard Bore Possible

# Princeton

LAYOUT OPTIONS



STANDARD



TALL




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC		SC/HC		SC/HC	
	1/8	SC/HC		SC/HC		SC/HC	
	1/10	SC/HC					
	2/0	SC/HC		SC/HC		SC/HC	
	2/2	SC/HC					
	2/4	SC/HC		SC/HC		SC/HC	
	2/6	SC/HC	SC/MC	SC/HC		SC/HC	SC
	2/8	SC/HC	SC/MC	SC/HC		SC/HC	SC
	2/10	SC/HC					
	3/0	SC/HC	SC/MC	SC/HC		SC/HC	SC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Smooth Surface



Cove & Bead Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:

1/6, 2/0, 2/4, 2/6, 2/8, 3/0

# Camden

LAYOUT OPTIONS



STANDARD



BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0 - N/A		8/0 - N/A	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC					
	1/8	SC/HC					
	1/10	SC/HC					
	2/0	SC/HC					
	2/2	SC/HC					
	2/4	SC/HC					
	2/6	SC/HC	SC				
	2/8	SC/HC	SC				
	2/10	SC/HC					
	3/0	SC/HC	SC				

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Textured Surface



Cove & Bead Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:

1/4, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 MC = Solid Mineral Core Construction  
 ⓧ = No Standard Bore Possible

# Craftsman III

LAYOUT OPTIONS



NARROW



STANDARD




BI-FOLD




Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0 - N/A	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
NARROW WIDTH	1/0	SC/HC		SC/HC			
	1/2	SC/HC		SC/HC			
	1/3	SC/HC		SC/HC			
	1/4	SC/HC		SC/HC			
	1/6	SC/HC	SC	SC/HC			
	1/8	SC/HC		SC/HC			
	1/10	SC/HC		SC/HC			
STANDARD WIDTH	2/0	SC/HC	SC	SC/HC			
	2/2	SC/HC		SC/HC			
	2/4	SC/HC	SC	SC/HC			
	2/6	SC/HC	SC	SC/HC	SC		
	2/8	SC/HC	SC	SC/HC	SC		
	2/10	SC/HC	SC	SC/HC			
	3/0	SC/HC	SC	SC/HC	SC		

6/8	
1-3/8"	
Bi-Fold	
2 DOOR	
2/0	SC/HC
2/4	
2/6	SC/HC
2/8	
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	
5/0	SC/HC
5/4	
6/0	SC/HC



Smooth Surface



Craftsman Sticking

# Avalon

LAYOUT OPTIONS



STANDARD



BI-FOLD




Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0 - N/A		8/0 - N/A	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC					
	1/8	SC/HC					
	1/10	SC/HC					
	2/0	SC/HC					
	2/2	SC/HC					
	2/4	SC/HC					
	2/6	SC/HC	SC				
	2/8	SC/HC	SC				
	2/10	SC/HC					
	3/0	SC/HC	SC				

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Textured Surface



Cove & Bead Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:  
1/6, 2/0, 2/4, 2/6, 2/8, 3/0

SC = Solid Particle Core Construction  
HC = Hollow Core Construction  
MC = Solid Mineral Core Construction  
⊗ = No Standard Bore Possible

# Coventry

LAYOUT OPTIONS



NARROW

STANDARD


TALL

BI-FOLD

Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
NARROW WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC	SC	SC		SC	
	1/8	SC/HC		SC		SC	
STANDARD WIDTH	1/10	SC/HC					
	2/0	SC/HC	SC	SC		SC	
	2/2	SC/HC					
	2/4	SC/HC	SC	SC		SC	
	2/6	SC/HC	SC/MC	SC	SC	SC	
	2/8	SC/HC	SC/MC	SC	SC/MC	SC	
	2/10	SC/HC	SC				
	3/0	SC/HC	SC/MC	SC	SC/MC	SC	

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	
2/6	SC/HC
2/8	
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	
5/0	SC/HC
5/4	
6/0	SC/HC



Smooth Surface



Cove & Bead Sticking

# Provincial

LAYOUT OPTIONS



NARROW



STANDARD



BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0 - N/A		8/0 - N/A	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
NARROW WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC					
	1/8	SC/HC					
	1/10	SC/HC					
STANDARD WIDTH	2/0	SC/HC					
	2/2	SC/HC					
	2/4	SC/HC					
	2/6	SC/HC	SC				
	2/8	SC/HC	SC				
	2/10	SC/HC					
	3/0	SC/HC	SC				

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Textured Surface




Ovolo Sticking


SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 MC = Solid Mineral Core Construction  
 ☒ = No Standard Bore Possible

# Rockport

LAYOUT OPTIONS




STANDARD



TALL




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC	SC	SC/HC		SC/HC	
	1/8	SC/HC		SC/HC		SC/HC	
	1/10	SC/HC					
	2/0	SC/HC	SC	SC/HC		SC/HC	
	2/2	SC/HC					
	2/4	SC/HC	SC	SC/HC		SC/HC	
	2/6	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/8	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/10	SC/HC	SC				
	3/0	SC/HC	SC	SC/HC	SC	SC/HC	SC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Smooth Surface



Cove & Bead Sticking

# Conmore

LAYOUT OPTIONS



STANDARD




BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0 - N/A	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC		SC/HC			
	1/8	SC/HC		SC/HC			
	1/10	SC/HC					
	2/0	SC/HC		SC/HC			
	2/2	SC/HC					
	2/4	SC/HC		SC/HC			
	2/6	SC/HC	SC	SC/HC			
	2/8	SC/HC	SC	SC/HC			
	2/10	SC/HC					
	3/0	SC/HC	SC	SC/HC			

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	
2/6	SC/HC
2/8	
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	
5/0	SC/HC
5/4	
6/0	SC/HC



Smooth Surface



Step Sticking

SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 MC = Solid Mineral Core Construction  
 ☒ = No Standard Bore Possible

# Colonial

LAYOUT OPTIONS



NARROW



STANDARD



BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0 - N/A		8/0 - N/A	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
NARROW WIDTH	1/0	SC/HC					
	1/2	SC/HC					
	1/3	SC/HC					
	1/4	SC/HC					
	1/6	SC/HC					
	1/8	SC/HC					
STANDARD WIDTH	1/10	SC/HC					
	2/0	SC/HC					
	2/2	SC/HC					
	2/4	SC/HC					
	2/6	SC/HC	SC				
	2/8	SC/HC					
	2/10	SC/HC	SC				
	3/0	SC/HC	SC				

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Textured Surface



Ovolo Sticking

# Colonist


( Smooth )

LAYOUT OPTIONS




		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
NARROW WIDTH	1/0	SC/HC		SC/HC		SC/HC	
	1/2	SC/HC		SC/HC		SC/HC	
	1/3	SC/HC		SC/HC		SC/HC	
	1/4	SC/HC		SC/HC		SC/HC	
	1/6	SC/HC	SC	SC/HC	SC	SC/HC	SC
	1/8	SC/HC		SC/HC		SC/HC	
STANDARD WIDTH	1/10	SC/HC		SC/HC		SC/HC	
	2/0	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/2	SC/HC		SC/HC		SC/HC	
	2/4	SC/HC	SC	SC/HC	SC	SC/HC	SC
	2/6	SC/HC	SC/MC	SC/HC	SC	SC/HC	SC
	2/8	SC/HC	SC/MC	SC/HC	SC/MC	SC/HC	SC
	2/10	SC/HC	SC	SC/HC	SC	SC/HC	SC
	3/0	SC/HC	SC/MC	SC/HC	SC/MC	SC/HC	SC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Panel Detail



Smooth Surface



Cove & Bead Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:

1/6, 2/0, 2/4, 2/6, 2/8, 2/10, 3/0

SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 MC = Solid Mineral Core Construction  
 ☒ = No Standard Bore Possible

# Colonist

( Textured )

LAYOUT OPTIONS



NARROW




STANDARD



TALL



BI-FOLD



Panel Detail

		STANDARD				TALL	
HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
NARROW WIDTH	1/0	SC/HC		SC/HC		HC	
	1/2	SC/HC		SC/HC		HC	
	1/3	SC/HC		SC/HC		HC	
	1/4	SC/HC		SC/HC		HC	
	1/6	SC/HC		SC/HC		SC/HC	
	1/8	SC/HC		SC/HC		SC/HC	
STANDARD WIDTH	1/10	SC/HC		SC/HC		HC	
	2/0	SC/HC		SC/HC		SC/HC	
	2/2	SC/HC		SC/HC		SC/HC	
	2/4	SC/HC		SC/HC		SC/HC	
	2/6	SC/HC	SC/MC	SC/HC		SC/HC	
	2/8	SC/HC	SC/MC	SC/HC		SC/HC	
	2/10	SC/HC		SC/HC		SC/HC	
	3/0	SC/HC	SC/MC	SC/HC		SC/HC	

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	SC/HC
2/4	HC
2/6	SC/HC
2/8	HC
3/0	SC/HC
4 DOOR	
4/0	SC/HC
4/8	HC
5/0	SC/HC
5/4	HC
6/0	SC/HC



Textured Surface



Cove & Bead Sticking

6/8 Hollow Core 1-3/8" doors are stocked with fiber stiles in the following sizes:

1/0, 1/2, 1/4, 1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

# Mirror

For more details on  
Colonist Textured  
see page 34

LAYOUT OPTIONS




COLONIST  
TEXTURED



MIRROR  
TEXTURED



1" Bevel Mirror Edge



Ovolo Sticking

		STANDARD	
HEIGHT		6/8	
THICKNESS		1-3/8"	1-3/4"
Door Sizes			
STANDARD WIDTH	1/0		
	1/2		
	1/3		
	1/4		
	1/6		
	1/8		
	1/10		
	2/0	HC	
	2/2		
	2/4	HC	
	2/6	HC	
	2/8	HC	
	2/10		
	3/0	HC	

# Flush Doors



## SC Solid Particle Core CONSTRUCTION


Triple-bottom wood rail for added durability and ease of trimming  
(Note: Field-trimming can affect fire ratings. To ensure proper ratings, doors must be factory-trimmed by Reeb®)



**Fire Rating**  
UP TO 20 MINUTES  
1-3/4" ONLY



**Sound Benefits**  
REDUCED SOUND  
TRANSMISSION



## HC Hollow Core CONSTRUCTION

### Solid Particle Core (SC)

Solid, heavy construction - feels like real wood

**Stile:** Wood stiles for additional screw holding power

**Rail (6/8 height, 1-3/8" thickness doors):**

1" (single) top rail and 3" (triple) bottom rail, allowing the door to be field-trimmed up to 2"

**Rail (6/8 height, 1-3/4" thickness doors):**

1" (single) top rail and 2" (double) bottom rail, allowing the door to be field-trimmed up to 1"

**Rail (7/0 & 8/0 height):** All doors in 7/0 and 8/0 height have a single 1" top rail and a 2" bottom rail, allowing the door to be field-trimmed up to 1"

**Core:** Solid Particle Core manufactured for up to 20-minute fire label requirements

**Face:** Two-ply 1/8" thickness wood faces affixed to an MDF substrate.

**Height:** Available in 6/8, 7/0 & 8/0

**Finish:** Available in Birch, Lauan, Primed Hardboard and Oak

**Thickness:** Available in 1-3/8" & 1-3/4"

### Hollow Core (HC)

Lighter weight, economic alternative

**Stile:** Wood stiles for additional screw holding power

**Rail (6/8 height, 1-3/8" thickness doors):**

1" (single) fiber top rail and 3" (triple) fiber bottom rail, allowing the door to be trimmed up to 2"

**Rail (7/0 & 8/0 height, 1-3/8" thickness doors):**

1" fiber top rail and a 2" fiber bottom rail, allowing the door to be trimmed up to 1"


**Core:** Hollow Core

**Face:** Two-ply 1/8" thickness wood faces affixed to an MDF substrate.

**Height:** Available in 6/8, 7/0 & 8/0

**Finish:** Available in Birch, Lauan, Primed Hardboard and Oak

**Thickness:** Available in 1-3/8" & 1-3/4"



## Solid Wood Core

CONSTRUCTION



### Sound Benefits

REDUCED SOUND  
TRANSMISSION



## Solid Mineral Core

CONSTRUCTION

Recommended for  
light-commercial applications  
that require a 90-minute  
fire-rated door.



### Fire Rating

UP TO 90 MINUTES  
1-3/4" ONLY



### Sound Benefits

REDUCED SOUND  
TRANSMISSION

## Solid Wood Core (WC)

Heaviest, most durable construction

**Stile:** Wood stiles for additional screw  
holding power

**Rail (6/8 & 7/0 heights, 1-3/8" & 1-3/4"**  
**thickness doors):** 1" (single) wood top rail and  
2" (double) wood bottom rail, allowing the door  
to be trimmed up to 1"

**Core:** Solid Wood Core

**Face:** Two-ply 1/8" thickness wood faces  
affixed to an MDF Substrate

**Height:** 6/8 & 7/0

**Finish:** Available in Birch and Oak

**Thickness:** Available in 1-3/8" & 1-3/4"

## Solid Mineral Core (MC)

Dense construction provides additional weight  
and reduced sound transmission

**Stile:** Firestop with softwood edges

**Rail (6/8 & 7/0 heights, 1-3/4" thickness**  
**doors):** 2" (double) top rail and 2" (double)  
bottom rail

**Core:** Solid Mineral Core manufactured for up  
to 90-minute fire label requirements


**Face:** Two-ply 1/8" thickness wood faces  
affixed to an MDF substrate

**Height:** Available in 6/8 & 7/0

**Finish:** Available in Birch only

**Thickness:** Available in 1-3/4" only

# Flush Primed




Close-Up


HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC	SC/HC	SC/HC	SC/HC		
	1/2	SC/HC	SC/HC	SC/HC	SC/HC		
	1/3	SC/HC	SC/HC	SC/HC	SC/HC		
	1/4	SC/HC	SC/HC	SC/HC	SC/HC		
	1/6	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC
	1/8	SC/HC	SC/HC	SC/HC	SC/HC		
	1/10	SC	SC	SC/HC	SC/HC		
	2/0	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC
	2/2	SC	SC	SC/HC	SC/HC		
	2/4	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC
	2/6	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC
	2/8	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC
	2/10	SC	SC	SC/HC	SC/HC		SC
	3/0	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC	SC/HC

6/8 - N/A	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	
2/4	
2/6	
2/8	
3/0	
4 DOOR	
4/0	
4/8	
5/0	
5/4	
6/0	

# Flush Lauan



Close-Up



BI-FOLD



HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC		HC		HC	
	1/2	SC/HC		HC		HC	
	1/3	SC/HC		HC		HC	
	1/4	SC/HC		HC		HC	
	1/6	SC/HC	SC	SC/HC		HC	
	1/8	SC/HC		SC/HC		HC	
	1/10	SC/HC		HC		HC	
	2/0	SC/HC	SC/HC	SC/HC	SC	HC	
	2/2	SC/HC	SC	HC	SC	HC	
	2/4	SC/HC	SC	SC/HC	SC	HC	
	2/6	SC/HC	SC/HC	SC/HC	SC/HC	HC	
	2/8	SC/HC	SC/HC	SC/HC	SC/HC	HC	
	2/10	SC/HC	SC	HC	SC	HC	
	3/0	SC/HC	SC/HC	SC/HC	SC/HC	HC	

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	HC
2/4	HC
2/6	HC
2/8	HC
3/0	HC
4 DOOR	
4/0	HC
4/8	HC
5/0	HC
5/4	HC
6/0	HC

Hollow Core Flush Lauan 1-3/8" doors are also stocked in 6/0 and 6/6 heights

SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 WC = Solid Wood Core Construction  
 MC = Solid Mineral Core Construction

# Flush Birch




**BI-FOLD**

HEIGHT		6/8		7/0		8/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes							
STANDARD WIDTH	1/0	SC/HC	SC/HC	SC/HC	SC/HC	SC	SC/HC
	1/2	SC/HC	SC/HC	SC/HC	SC/HC		SC/HC
	1/3	SC/HC	SC/HC	SC/HC	SC/HC		SC/HC
	1/4	SC/HC	SC/HC	SC/HC	SC/HC		SC/HC
	1/6	SC/HC	SC/HC	SC/HC	SC/HC		SC/HC
	1/8	SC/HC	SC/HC	SC/HC	SC/HC		SC/HC
	1/10	SC/HC	SC/HC	SC/HC	SC/HC		SC/HC
	2/0	SC/HC/WC	SC/HC/WC	SC/HC	SC/HC/WC	SC/HC	SC/HC
	2/2	SC/HC	SC/HC	SC/HC	SC/HC	HC	SC/HC
	2/4	SC/HC/WC	SC/HC/WC	SC/HC	SC/HC/WC	SC/HC	SC/HC
	2/6	SC/HC/WC	SC/HC/WC	SC/HC	SC/HC/WC	SC/HC	SC/HC
	2/8	SC/HC/WC	SC/HC/WC/MC	SC/HC	SC/HC/WC	SC/HC	SC/HC
	2/10	SC/HC	SC/HC/WC	SC/HC	SC/HC/WC	HC	SC/HC
	3/0	SC/HC/WC	SC/HC/WC/MC	SC/HC	SC/HC/WC	SC/HC	SC/HC
	3/4		WC		WC		
	3/6	SC/HC	SC/HC/WC		SC/HC/WC		SC/HC
	3/8		WC		WC		
	4/0		WC		WC		

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	HC
2/4	HC
2/6	HC
2/8	HC
3/0	HC
4 DOOR	
4/0	HC
4/8	HC
5/0	HC
5/4	HC
6/0	HC

Hollow Core Flush Birch 1-3/8" doors are also stocked in 6/0 and 6/6 heights

# Flush Oak



BI-FOLD

IMPERIAL OAK

HEIGHT		6/8		7/0	
THICKNESS		1-3/8"	1-3/4"	1-3/8"	1-3/4"
Door Sizes					
STANDARD WIDTH	1/0	HC			
	1/2	HC			
	1/3	HC			
	1/4	HC			
	1/6	SC/HC			
	1/8	SC/HC			
	1/10	SC/HC			
	2/0	SC/HC	SC		
	2/2	SC/HC			
	2/4	SC/HC	SC		
	2/6	SC/HC	SC/WC		SC/WC
	2/8	SC/HC	SC/WC		SC/WC
	2/10	SC/HC	SC		
	3/0	SC/HC	SC/WC		SC/WC

6/8	
1-3/8"	
Bi-Fold Sizes	
2 DOOR	
2/0	HC
2/4	HC
2/6	HC
2/8	HC
3/0	HC
4 DOOR	
4/0	HC
4/8	HC
5/0	HC
5/4	HC
6/0	HC

6/8	
1-3/8"	
Door Sizes	
1/0	
1/2	
1/3	
1/4	
1/6	HC
1/8	
1/10	
2/0	HC
2/2	
2/4	HC
2/6	HC
2/8	HC
2/10	HC
3/0	HC

SC = Solid Particle Core Construction  
 HC = Hollow Core Construction  
 WC = Solid Wood Core Construction  
 MC = Solid Mineral Core Construction

# Jambs

The jambs are the component of a pre-hung unit to which the door is affixed. They are available in a variety of species and either paintable or stainable options to match the door.

Please check with your local dealer for availability.

## Jamb Profiles

Flat jambs are a popular choice and are often accompanied by a stop. Split jambs are adjustable to fit a range of jamb widths. Jamb options are based on your location and market.

Please check with your local dealer for availability.



Oak Veneered

Pine Veneered

Primed Pine

# Fire Door Jambs

Fire-rated doors are often used for house-to-garage applications or as entrances to multi-family dwellings. If a fire-rating is desired, it is important to use fire-rated jambs. All 20 minute fire door frames are available in 4-9/16", 5-1/4", or 6-9/16" widths.

Clear Pine

Primed

# Hinges

Hinges allow the door to open and close. For increased durability and smooth operation, it is recommended to use ball-bearing hinges for heavier doors, such as solid particle or solid mineral core doors.

When using a standard 1-3/8" thick door, a 3-1/2" x 3-1/2" hinge is typically used.

When using a 1-3/4" thick door, a 4" x 4" hinge is typically used.



Non-Ball Bearing Square



Non-Ball Bearing Radius

Non-Ball Bearing Hinges	US1D	US3	US4B	US5	US10B	US15	US26	US26D
3-1/2" x 3-1/2" RSP Square	✓	✓		✓	✓	✓	✓	✓
3-1/2" x 3-1/2" RSP Radius	✓	✓	✓	✓	✓	✓	✓	✓
4" x 4" RSP Square		✓		✓	✓	✓	✓	✓
4" x 4" RSP Radius	✓	✓	✓	✓	✓	✓	✓	✓



Ball Bearing Square



Ball Bearing Radius

Ball Bearing Hinges	US1D	US3	US4B	US5	US10B	US15	US26	US26D
3-1/2" x 3-1/2" RSP Square		✓		✓	✓	✓	✓	✓
3-1/2" x 3-1/2" RSP Radius	✓	✓	✓	✓	✓	✓	✓	✓
4" x 4" RSP Square	✓	✓		✓	✓	✓	✓	✓
4" x 4" RSP Radius	✓	✓	✓	✓	✓	✓	✓	✓

## Fire Door Hinges

When completing a fire-rated unit, it is important to utilize self-closing or commercial hinges.



**4" x 4"**  
Self-Closing Hinge

4" Self Closing Hinges	US1D	US3	US4B	US10B	US15	US26	US26D
4" x 4"	✓	✓	✓	✓	✓	✓	✓



**4-1/2" x 4-1/2"**  
Commercial Hinge

4-1/2" Commercial Hinges	US1D	US3	US4B	US10B	US26	US26D
4-1/2" x 4-1/2"	✓	✓	✓	✓	✓	✓
4-1/2" x 4-1/2" Ball Bearing		✓		✓	✓	✓

## Hinge Finishes



US1D



US3



US4B




US5



US10B



US15



US26



US26D

# Hardware

Locksets are available in either a knob or lever style and provide tough, reliable performance and enduring style. They are available in multiple finishes to match the hinges used on the door.

## Standard Residential Series Locks



**Flair**



**Accent**



**Plymouth**

---

## Builder's Series Locks



**LaSalle**



**Torino**



**Corona**

---

# Fire Door Hardware

Light commercial locksets are recommended to be used with a 60 or 90 minute fire rated door unit. Door closers aid the door in closing and are recommended to be used with 4-1/2" x 4-1/2" commercial ball bearing hinges.



### Light Commercial Entry Lock

Recommended to be used with 60 or 90 minute door units.



### 5300 Series Door Closer

Recommended to be used with 4-1/2" x 4-1/2" commercial hinges.

# Barn Door Track Hardware

Goldberg® Hardware is a perfect fit for modern, contemporary, and rustic applications and works well with heavier solid particle core doors. Barn doors allow the flexibility to enhance an entire room with a unique accent piece while also adding more functionality to your space.

Available in Black, Silver and Architectural Bronze.



Privacy Latch



Roller Hanger



6" Flush Pull



7" Pull Handle



For more light commercial options, view the latest Reeb Commercial Doors catalog online at [reeb.com/catalogs](http://reeb.com/catalogs).



*There is a unique warmth and sophistication that can only be found in real wood.*

View the latest Reeb Interior Stile and Rail Doors catalog online at [reeb.com/catalogs](http://reeb.com/catalogs).



# Warranty

## Handling & Care

Store doors flat on a level surface in a dry, well-ventilated building. Cover to keep clean, but allow air circulation. The utility or structural strength of the door must not be impaired in the fitting of the door, the application of hardware, or cutting and altering the door for lights, louvers, panels or any other special details.

As a general rule, use three hinges for all interior doors. For hollow-core doors weighing less than 50 pounds or under 6/8 in height, two hinges are acceptable. All doors 7/6 or above require four hinges. Allow a fitting clearance of 1/16" on the hinge side and 1/8" on the lock side.

Immediately after fitting or cutting for closure, weatherstrip, and/or threshold and before hanging on the job - any interior or exterior door must receive an application of primer and two coats of high-quality paint, varnish or lacquer on all edges, including the top and bottom. Adequate drying time must be allowed between coats. For job-site finishing, do not use water-thinned paints unless an oil-base prime coat is first applied.

---

## Hanging

If stops and jambs are not set plumb and in a true plane, jambs are not properly squared, or hinges are not set in a straight line, opening and closing the door will result in stress and cause distortion. Three hinges will restrain distortion better than two, but must be set with greater care to have all three in perfect alignment.

---



## Steves Limited 5 Year Warranty

Steves and Sons warrants all doors sold under their warranty to be free from manufacturing defects in material and workmanship for a period of five (5) years from original date of shipment. This warranty is subject to the limitations and conditions of the full warranty which can be found at [reeb.com/warranties](http://reeb.com/warranties) or [www.stevesdoors.com](http://www.stevesdoors.com).


### Finish Requirements

Finish should be applied immediately after fitting, making certain that all six sides are primed and given two coats of paint, varnish or sealer before hanging. In too many instances, the doors are hung prior to finishing, meaning the bottom edge likely receives no paint or sealer. The bottom edge is the most vulnerable point on the door.

# Molded Door Specifications


Door Style	Surface	Sticking	Top Rail	Bottom Rail	Lock Rail	Height
<i>Madison - 1 Panel Square Top</i>	<i>Smooth</i>	<i>Craftsman</i>	<i>4-3/4"</i>	<i>8-1/4"</i>	<i>N/A</i>	<i>6/8</i>
<i>Monroe - 2 Panel Square Top</i>	<i>Smooth</i>	<i>Craftsman</i>	<i>4-3/4"</i>	<i>11-1/8"</i>	<i>7"</i>	<i>6/8</i>
<i>Monroe - 2 Panel Square Top</i>	<i>Smooth</i>	<i>Craftsman</i>	<i>4-3/4"</i>	<i>11-1/8"</i>	<i>7"</i>	<i>8/0</i>
<i>Cambridge - 2 Panel Square Top</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>4-1/4"</i>	<i>9-1/8"</i>	<i>7"</i>	<i>6/8</i>
<i>Cambridge - 2 Panel Square Top</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>6-1/4"</i>	<i>11-1/8"</i>	<i>7"</i>	<i>7/0</i>
<i>Cambridge - 2 Panel Square Top</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>4-7/16"</i>	<i>8-15/16"</i>	<i>7"</i>	<i>8/0</i>
<i>Corvado - 2 Panel Plank Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>4-1/2"</i>	<i>8-3/4"</i>	<i>6-3/4"</i>	<i>6/8</i>
<i>Continental - 2 Panel Round Top</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>5-1/4"</i>	<i>10-13/16"</i>	<i>4-3/16"</i>	<i>6/8</i>
<i>Continental - 2 Panel Round Top</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>7-1/4"</i>	<i>12-13/16"</i>	<i>4-3/16"</i>	<i>7/0</i>
<i>Continental - 2 Panel Round Top</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>5-1/4"</i>	<i>11"</i>	<i>4-1/4"</i>	<i>8/0</i>
<i>Santa Fe - 2 Panel Round Top Plank</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>4-3/8"</i>	<i>9-7/8"</i>	<i>7"</i>	<i>6/8</i>
<i>Santa Fe - 2 Panel Round Top Plank</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>6-3/8"</i>	<i>11-7/8"</i>	<i>7"</i>	<i>7/0</i>
<i>Santa Fe - 2 Panel Round Top Plank</i>	<i>Smooth</i>	<i>Ovolo</i>	<i>4-3/8"</i>	<i>9-7/8"</i>	<i>7"</i>	<i>8/0</i>
<i>Princeton - 2 Panel Arch Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>5-3/8"</i>	<i>8-1/4"</i>	<i>3-3/4"</i>	<i>6/8</i>
<i>Princeton - 2 Panel Arch Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>7-3/8"</i>	<i>10-1/4"</i>	<i>3-3/4"</i>	<i>7/0</i>
<i>Princeton - 2 Panel Arch Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>5-1/2"</i>	<i>8-1/2"</i>	<i>3-3/4"</i>	<i>8/0</i>
<i>Camden - 2 Panel Arch Top</i>	<i>Textured</i>	<i>Cove &amp; Bead</i>	<i>5"</i>	<i>9"</i>	<i>3-3/4"</i>	<i>6/8</i>
<i>Craftsman III - 3 Panel Square Top</i>	<i>Smooth</i>	<i>Craftsman</i>	<i>4-5/8"</i>	<i>8-15/16"</i>	<i>N/A</i>	<i>6/8</i>
<i>Craftsman III - 3 Panel Square Top</i>	<i>Smooth</i>	<i>Craftsman</i>	<i>6-5/8"</i>	<i>10-15/16"</i>	<i>N/A</i>	<i>7/0</i>
<i>Avalon - 3 Panel Square Top</i>	<i>Textured</i>	<i>Cove &amp; Bead</i>	<i>4-13/16"</i>	<i>8"</i>	<i>N/A</i>	<i>6/8</i>
<i>Coventry - 4 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>4-1/2"</i>	<i>8-3/4"</i>	<i>6-3/4"</i>	<i>6/8</i>
<i>Provincial - 4 Panel Arch Top</i>	<i>Textured</i>	<i>Ovolo</i>	<i>5"</i>	<i>9-1/4"</i>	<i>7"</i>	<i>6/8</i>
<i>Rockport - 5 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>4-1/2"</i>	<i>8-1/2"</i>	<i>N/A</i>	<i>6/8</i>
<i>Rockport - 5 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>6-1/2"</i>	<i>10-1/2"</i>	<i>N/A</i>	<i>7/0</i>
<i>Rockport - 5 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>4-5/8"</i>	<i>10-1/8"</i>	<i>N/A</i>	<i>8/0</i>
<i>Conmore - 5 Panel Square Top</i>	<i>Smooth</i>	<i>Step Sticking</i>	<i>6-1/2"</i>	<i>10-3/4"</i>	<i>N/A</i>	<i>6/8</i>
<i>Conmore - 5 Panel Square Top</i>	<i>Smooth</i>	<i>Step Sticking</i>	<i>8-1/2"</i>	<i>12-3/4"</i>	<i>N/A</i>	<i>7/0</i>
<i>Colonial - 6 Panel Square Top</i>	<i>Textured</i>	<i>Ovolo</i>	<i>4-1/4"</i>	<i>9-1/16"</i>	<i>7"</i>	<i>6/8</i>
<i>Colonist - 6 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>4-1/8"</i>	<i>8-1/4"</i>	<i>6-7/8"</i>	<i>6/8</i>
<i>Colonist - 6 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>6-1/8"</i>	<i>10-1/4"</i>	<i>6-7/8"</i>	<i>7/0</i>
<i>Colonist - 6 Panel Square Top</i>	<i>Smooth</i>	<i>Cove &amp; Bead</i>	<i>5-1/16"</i>	<i>8-7/16"</i>	<i>6-7/8"</i>	<i>8/0</i>
<i>Colonist - 6 Panel Square Top</i>	<i>Textured</i>	<i>Cove &amp; Bead</i>	<i>4-1/4"</i>	<i>8-1/4"</i>	<i>6-7/8"</i>	<i>6/8</i>
<i>Colonist - 6 Panel Square Top</i>	<i>Textured</i>	<i>Cove &amp; Bead</i>	<i>6-1/4"</i>	<i>10-1/4"</i>	<i>6-7/8"</i>	<i>7/0</i>
<i>Colonist - 6 Panel Square Top</i>	<i>Textured</i>	<i>Cove &amp; Bead</i>	<i>4-1/4"</i>	<i>8-1/4"</i>	<i>6-7/8"</i>	<i>8/0</i>
Mirror Door		Sticking	Top Rail	Bottom Rail	Lock Rail	Height
<i>Colonist - 6 Panel Square Top Textured</i>		<i>Cove &amp; Bead</i>	<i>4-1/2"</i>	<i>8-1/4"</i>	<i>6-7/8"</i>	<i>6/8</i>
<i>Mirror Side Textured</i>		<i>Ovolo</i>	<i>4-1/4"</i>	<i>9-3/8"</i>	<i>N/A</i>	<i>6/8</i>

 **Bethlehem, PA**  
1000 Maloney Cir.  
Bethlehem, PA 18015  
(800) 862-8622 voice  
(800) 772-7332 fax

 **Barclay, MD**  
1315 Goldsboro Rd.  
Barclay, MD 21607  
(800) 825-8331 voice  
(800) 331-9387 fax

 **Mocksville, NC**  
346 Bethel Church Rd.  
Mocksville, NC 27028  
(800) 642-0886 voice  
(800) 618-0620 fax

 **Providence, RI**  
19 Business Park Dr.  
Smithfield, RI 02917  
(800) 343-5703 voice  
(800) 388-5979 fax

 **Syracuse, NY**  
7475 Henry Clay Blvd.  
Liverpool, NY 13088  
(800) 422-5224 voice  
(800) 531-7332 fax



**PART# REEBFM17**

VERSION 1.0.0