

MODERN
MARVIN SIGNATURE® COLLECTION





THE SPIRIT OF MODERN DESIGN LIVES ON.

BORN FROM AND INFORMED BY THE
NEEDS OF ARCHITECTS AND BUILDERS,
OUR **MODERN** LINE IS INTENTIONAL IN
BOTH PROCESS AND PRODUCT.

We've considered how every detail can serve you and your vision,
guided by the quality and innovation that only Marvin can deliver.

THIS IS DESIGN IN YOUR HANDS.

THIS IS OUR MODULAR SYSTEM.

Every product works together as part of a visual system to help you design and configure with ease and confidence. Consistent sightlines across all products—along with special innovations like our integrated mull channel—maintain the clean aesthetic so central to modern design.

Pictured below: Modern Direct Glaze and Casement windows (left) and the Modern Multi-Slide door (right)
Certified mulling options are available

CONSISTENT SIGHTLINES

MINIMIZE SYSTEM
ALIGNMENT GUESSWORK

INTEGRATED
MULL CHANNEL

PRESERVES SIGHTLINES AND SUPPORTS
STRUCTURAL PERFORMANCE

CRANK OUT AND PUSH OUT
CASEMENTS AVAILABLE

MAINTAINS CONSISTENT
NARROW SIGHTLINES
ACROSS ALL PRODUCTS

PREFABRICATED AND
PRE-CONFIGURED


COMPONENTS SAVE
ON INSTALLATION TIME

THIS IS POWER IN SIMPLICITY.

THIS IS OUR PROPRIETARY FRAME.


A new frame design reimagines how modern windows and doors can perform. From exterior to interior, our proprietary High-Density Fiberglass infuses the Modern window and door frame with superior strength and thermal performance. The frame also features an integrated mull channel that enables mull reinforcement while maintaining sightlines and preserving thermal efficiency.

Pictured right: Modern Direct Glaze window cross-section



PROPRIETARY
FRAME DESIGN
HELPS KEEP INTERIOR
TEMPERATURES COMFORTABLE

BUILT-IN
DRYWALL RETURN
FOR EASY WALL INTEGRATION



THE FRAME'S INTEGRATED
MULL CHANNEL
ENABLES MULL REINFORCEMENT WITHOUT
ALTERING SIGHTLINES

THERMALLY EFFICIENT
TO PERFORM IN DEMANDING CLIMATES

DURABLE FINISH
MEETS THE HIGHEST INDUSTRY STANDARDS

REVOLUTIONARY HIGH-DENSITY
FIBERGLASS MATERIAL

THIS IS PERFORMANCE BEYOND EXPECTATIONS.

THIS IS HIGH-DENSITY FIBERGLASS.

We envisioned more performance potential for modern windows and doors. So we developed High-Density Fiberglass, a revolutionary material that echoes the look of its modern counterparts with better thermal efficiency.

Pictured above: Modern Direct Glaze mull window cross-section



ELEMENTAL
ALUMINUM
INTERIOR
WITH LOW-GLOSS FINISH

STRENGTH AND DURABILITY
RATED UP TO PG45
FOR IMPRESSIVE PERFORMANCE

DETAILS THAT
ENHANCE
THE VIEW
LIKE CONCEALED FASTENERS,
MINIMAL BLACK SPACER BARS,
AND BLACK SEALANT

THIS IS HOW IT ALL

COMES TOGETHER.

Combine product ingenuity with pure modern aesthetics and the result is truly stunning. Our Modern line is made to be built big and perform at scale, complemented by the power of critical design details. A low-gloss aluminum interior adds an elemental feel. Black spacer bars and black sealant engineered to maintain a clean daylight opening minimizes visual distractions. And internal covers completely disguise fasteners for clean, crisp edges.

**Pictured left: Modern Multi-Slide door
with a Clear Anodized interior finish**

THIS WAS MADE FOR YOU.

WE PARTNERED WITH ARCHITECTS AND BUILDERS TO DEVELOP A PROCESS THAT ANSWERS THEIR NEEDS AT EVERY STEP ALONG THE WAY.



DELIVERY

We worked to create packaging and delivery systems that help you plan better and make the best use of your time and resources.



It begins with **PRODUCT WEIGHTS** listed on the quote and order confirmation – so you can plan proper equipment and resources in advance. We also provide prominent **WEIGHT LABELS** on every Modern product for easy on-site reference.



All products are packaged to protect components during shipping and handling. Ergonomic **LIFT POINTS** on each end of the unit help you leverage heavy products. Staple-free **CARDBOARD BOOTS** are fully wrapped around each corner. Dual skid plates provide rigidity and maneuverability, so you can slide products across different floor surfaces.

OTHER CONSIDERATIONS

- + Glass is covered with protective film
- + Each unit is stretch wrapped



INSTALLATION

On the job site, efficiency is key. So we created thoughtful products and accessories that ensure the installation runs smoothly.



A **JOB BOX** contains all the important parts and documentation you need, in one convenient place. Specially stocked according to your order, inside every job box you'll find:

- + Product hardware
- + Installation screws
- + Injection sealant
- + Installation instructions
- + Order information
- + Warranty registration
- + Touch-up and repair kits
- + And more

Never lose time tracking down an extra part or reference material.


OTHER CONSIDERATIONS

- + Pre-fabricated and pre-configured components reduce install time
- + Drywall recess in the frame accepts a drywall return for seamless integration



MADE TO BE BUILT BIG AND PERFORM AT SCALE.

MODERN WINDOWS



INTERIOR VIEW – PUSH OUT AWNING SHOWN IN EBONY WITH MATTE BLACK HARDWARE



INTERIOR VIEW – CRANK OUT AWNING SHOWN IN EBONY WITH MATTE BLACK HARDWARE

MODERN AWNING WINDOW

FEATURES
Crank Out and Push Out available
Sleek and modern form
Numerous sizes and configurations available, including right- or left-hand operating
Screens are intentionally designed to achieve a cohesive look with the window
Frame recess accepts a drywall return
Horizontal or vertical ribbon mulling capabilities
HARDWARE FOR ALL AWNING
Concealed multi-point lock system
One locking lever to engage or disengage multi-point locks
Stainless steel hinges
Proprietary Crank Out and Push Out designed hardware
HARDWARE FOR PUSH OUT
Discreet, nested handle at the sash and frame
HARDWARE FOR CRANK OUT
Exclusive rotating handle design

GLASS OPTIONS
Dual or triple-pane insulated glass
Interior cover depths vary based on glass thickness
Black spacer and dark silicone sealant
Low E1, E2, E3, ELR, or ERS glass options
Specialty glass: frosted, obscure, and gray or bronze tint
Argon or Krypton-Argon blend gas
CONFIGURATIONS AND MULLING
Jamb depth4 1/2"
Awning to awning mulled frames5 9/16" wide
Seamless mulled assemblies with aluminum reinforcement
THERMAL PERFORMANCE
Dual-pane IG low E2 with Argon0.28 U-Factor

UNIT TYPE	AIR TESTED TO PSF	WATER TESTED TO PSF	DESIGN PRESSURE	CERTIFICATION RATING	MAX FRAME SIZE UNIT	
AWNING					WIDTH	HEIGHT
CRANK OUT	1.57	12.1	50	CW-PG50-FW	64"	96"
CRANK OUT	1.57	12.1	45	LC-PG45-FW	96"	64"
PUSH OUT	1.57	12.1	45	CW-PG45-FW	96"	64"
CRANK OUT	1.57	12.1	50	CW-PG50-FW	72"	72"
PUSH OUT	1.57	12.1	50	CW-PG50-FW	89"	48"
MULL ASSEMBLIES					WIDTH	HEIGHT
ALL PRODUCTS	1.57	12.1	40	CW-PG40-FW	168"	96"
ALL PRODUCTS	1.57	12.1	40	CW-PG40-FW	96"	168"

For the most complete technical information, visit marvin.com or talk with your Modern dealer.



INTERIOR VIEW – PUSH OUT CASEMENTS SHOWN IN EBONY WITH MATTE BLACK HARDWARE



EXTERIOR VIEW – CASEMENTS SHOWN IN EBONY

MODERN CASEMENT WINDOW

FEATURES

- Crank Out and Push Out available
- Sleek and modern form
- Numerous sizes and configurations available, including right- or left-hand operating
- Screens are intentionally designed to achieve a cohesive look with the window
- Sash can slide across frame for easy wash mode
- Frame recess accepts a drywall return
- Horizontal or vertical ribbon mulling capabilities

HARDWARE FOR ALL CASEMENT

- Concealed multi-point lock system
- One locking lever to engage or disengage multi-point locks
- Stainless steel hinges
- Proprietary Crank Out and Push Out designed hardware

HARDWARE FOR PUSH OUT

- Discreet, nested handle at the sash and frame
- Optional low or mid-height handle and lock placement

HARDWARE FOR CRANK OUT

- Exclusive rotating handle design

GLASS OPTIONS

- Dual or triple-pane insulated glass
- Interior cover depths vary based on glass thickness
- Black spacer and dark silicone sealant
- Low E1, E2, E3, ELR, or ERS glass options
- Specialty glass: frosted, obscure, and gray or bronze tint
- Argon or Krypton-Argon blend gas

CONFIGURATIONS AND MULLING

- Casement to casement mulled frames 5 7⁄16" wide
- Seamless mulled assemblies with aluminum reinforcement

THERMAL PERFORMANCE

- Dual-pane IG low E2 with Argon 0.28 U-Factor

UNIT TYPE	AIR TESTED TO PSF	WATER TESTED TO PSF	DESIGN PRESSURE	CERTIFICATION RATING	MAX FRAME SIZE UNIT	
CASEMENT					WIDTH	HEIGHT
CRANK OUT AND PUSH OUT	1.57	12.1	50	CW-PG50-FW	36"	102"
CRANK OUT AND PUSH OUT	1.57	12.1	50	CW-PG50-FW	40"	96"
CRANK OUT AND PUSH OUT	1.57	12.1	50	CW-PG50-FW	44"	92"
MULL ASSEMBLIES					WIDTH	HEIGHT
ALL PRODUCTS	1.57	12.1	40	CW-PG40-FW	168"	96"
ALL PRODUCTS	1.57	12.1	40	CW-PG40-FW	96"	168"

For the most complete technical information, visit marvin.com or talk with your Modern dealer.



EXTERIOR VIEW – DIRECT GLAZE SHOWN IN EBONY

FEATURES

- Large expanses of glass for maximum views with numerous configurations and sizes available
- Rectangular and polygon shapes
- Frame recess accepts a drywall return
- Horizontal or vertical ribbon mulling capabilities
- Non-certified mulling capabilities

GLASS OPTIONS

- Dual or triple-pane insulated glass
- Interior cover depths vary based on glass thickness
- Argon or Krypton-Argon gas blend
- Black spacer and silicone sealant
- Low E1, E2, E3, ELR, or ERS glass options
- Specialty glass: frosted, obscure, and gray or bronze tint

MULLING

- Mulled frames are less than 3" wide
- Approximate 3" frame divider simulates a mulled Direct Glaze frame

CONFIGURATIONS

- Rectangle /square
- Isosceles triangle
- Right triangle, right or left
- Trapezoid, right or left
- Pentagon

SIZING

Max frame size certified	141 3⁄8" x 93 3⁄8"
Jamb depth	4 1⁄2"

SINGLE UNIT
PERFORMANCE RATINGS

Air tested to PSF	6.24
Water tested to PSF	7.5
Performance grade	CW-PG40-FW
Max frame size height	93 3⁄8"
Max frame size width	141 3⁄8"

VERTICAL OR HORIZONTAL MULLED UNITS
PERFORMANCE RATINGS

Air tested to PSF	1.57
Water tested to PSF	6.0
Performance grade	CW-PG40-FW
Max frame size height	96"
Max frame size width	168"
Max tributary width or height	84"

THERMAL PERFORMANCE

Dual-pane IG low E2 with Argon	0.28 U-Factor
--------------------------------	---------------


For the most complete technical information, visit marvin.com or talk with your Modern dealer.

PERFORMANCE ON A GRANDER SCALE.


MODERN DOORS



MODERN SWINGING DOOR



EXTERIOR VIEW – OUTSWING DOOR SHOWN IN GUNMETAL WITH MATTE BLACK HARDWARE



EXTERIOR VIEW – INSWING DOOR SHOWN IN GUNMETAL WITH MATTE BLACK HARDWARE

FEATURES

- 1 and 2 panel units, inswing and outswing
- Unequal panel widths
- Minimalist handles
- Two 7" square barrel hinges for all door heights
- Low-profile, performance, and saddle sills

HARDWARE

- Minimalist hardware with multi-point lock
- Sleek design for unobstructed views
- 7" adjustable hinge

GLASS OPTIONS

- Dual or triple-pane insulated glass
- Argon or Krypton-Argon blend gas
- Black spacer and dark silicone sealant
- Low E1, E2, E3, ELR, or ERS glass options
- Specialty glass: frosted, obscure, and gray or bronze tint

ADD-ONS

- Lock status sensor
- Retractable screens

PERFORMANCE GRADES

O	Performance Sill	up to CW-PG40-FD
O	Low Profile Sill	up to CW-PG30-FD
O or X	Performance Sill	up to LC-PG40-SHD
O or X	Low Profile Sill	up to LC-PG30-SHD
XO OX XX	Performance Sill	up to LC-PG40-SHD
XO OX XX	Low Profile Sill	up to LC-PG30-SHD

CONFIGURATIONS AND SIZING

- Max operator size: 4' x 12'
- Max stationary size: 8' x 12'
- 1-2 panel configurations
- Unequal panel widths
- Door to door mulling

UNIT TYPE		MIN FRAME SIZE UNIT		MAX FRAME SIZE UNIT	
UNI-DIRECTIONAL		WIDTH	HEIGHT	WIDTH	HEIGHT
O		16"	16"	144"	144"
X		20"	49"	48"	144"
OX OR XO		34"	49"	173"	144"
XX		38"	49"	96"	144"

O = Stationary Panel X = Operating Panel
* Panel quantity per unit limited to two panels



INTERIOR VIEW – MULTI-SLIDE DOOR SHOWN IN EBONY WITH MATTE BLACK HARDWARE

MODERN MULTI-SLIDE DOOR

FEATURES	
Large expanses of glass for maximum views with numerous configurations and sizes available	
Consistent panel thickness with narrow stiles and rails, regardless of configuration or size	
Minimalist hardware designed for superior functionality, features a sleek and modern form	
Low-profile, performance, and saddle sills in black or bronze	
HARDWARE	
Minimal pull and latch handles	
Keyed or non-keyed options available	
Multi-point lock	
Quad rollers with end adjustment	
GLASS OPTIONS	
Dual or triple-pane insulated glass	
Argon or Krypton-Argon blend gas	
Black spacer and dark silicone sealant	
Low E1, E2, E3, ELR, or ERS glass options	
Specialty glass: frosted, obscure, and gray or bronze tint	
ADD-ONS	
Automatic control	
Lock status sensor	
Retractable screen	
PERFORMANCE GRADES*	
Uni-directional stacked	up to LC-PG45-SD
Uni-directional pocket	up to LC-PG45-SD
Bi-parting stacked	up to LC-PG40-SD
Bi-parting pocket	up to LC-PG40-SD
THERMAL PERFORMANCE	
Dual-pane IG low E2 with Argon	0.28 U-Factor
MULTI-SLIDE CONFIGURATIONS AND SIZING	
Over 30 configurations available	
+ Uni-Directional configurations: 1 to 6 panels, available in stacked or pocket	
+ Bi-Parting configurations: 2 to 10 panels, available in stacked or pocket	
Sized to order up to 6' x 12' panels	
Meeting stiles are less than 3" wide	



For the most complete technical information, visit marvin.com or talk with your Modern dealer.

* Varies with sill type

MINIMUMS AND MAXIMUMS

MODERN MULTI-SLIDE DOOR STACKED

UNIT TYPE	MIN FRAME SIZE UNIT		MAX FRAME SIZE UNIT		MAX FRAME SIZE UNIT	
	Based on 6ft wide panels		Based on 6ft wide panels		Based on > 6ft wide panels*	
UNI-DIRECTIONAL	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT
OX OR XO	55 11⁄16"	62 3⁄64"	143 11⁄16"	144"	191 11⁄16"	120"
OXX OR XXO	80 13⁄16"	62 3⁄64"	212 13⁄16"	144"	284 13⁄16"	120"
OXXX OR XXXO	105 15⁄16"	62 3⁄64"	281 15⁄16"	144"	NA	NA
OXXXX OR XXXXO	131 1⁄16"	62 3⁄64"	351 1⁄16"	144"	NA	NA
OXXXXX OR XXXXXO	156 3⁄16"	62 3⁄64"	420 3⁄16"	144"	NA	NA

UNIT TYPE	MIN FRAME SIZE UNIT		MAX FRAME SIZE UNIT		MAX FRAME SIZE UNIT	
	Based on 6ft wide panels		Based on 6ft wide panels		Based on > 6ft wide panels*	
BI-PARTING	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT
OX - XO	109 3⁄4"	76 39⁄64"	285 3⁄4"	144"	381 3⁄4"	120"
OXX - XXO	160"	76 39⁄64"	424"	144"	568"	120"
OXXX - XXXO	210 1⁄4"	76 39⁄64"	562 1⁄4"	144"	NA	NA
OXXXX - XXXXO	260 1⁄2"	76 39⁄64"	700 1⁄2"	144"	NA	NA

O = Stationary Panel X = Operating Panel

MINIMUMS AND MAXIMUMS

MODERN MULTI-SLIDE DOOR POCKET

UNIT TYPE	MIN FRAME SIZE UNIT		MAX FRAME SIZE UNIT		MAX FRAME SIZE UNIT	
	Based on 6ft wide panels		Based on 6ft wide panels		Based on > 6ft wide panels*	
UNI-DIRECTIONAL	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT
PX OR XP	30 9⁄16"	68 19⁄64"	74 9⁄16"	144"	98 9⁄16"	120"
PXX OR XXP	55 11⁄16"	68 19⁄64"	143 11⁄16"	144"	191 11⁄16"	120"
PXXX OR XXXP	80 13⁄16"	68 19⁄64"	212 13⁄16"	144"	NA	NA
PXXXX OR XXXXP	105 15⁄16"	68 19⁄64"	281 15⁄16"	144"	NA	NA
PXXXXX OR XXXXXP	131 1⁄16"	68 19⁄64"	351 1⁄16"	144"	NA	NA
PXXXXXX OR XXXXXXP	156 3⁄16"	68 19⁄64"	420 3⁄16"	144"	NA	NA

UNIT TYPE	MIN FRAME SIZE UNIT		MAX FRAME SIZE UNIT		MAX FRAME SIZE UNIT	
	Based on 6ft wide panels		Based on 6ft wide panels		Based on > 6ft wide panels*	
BI-PARTING	WIDTH	HEIGHT	WIDTH	HEIGHT	WIDTH	HEIGHT
PX - XP	59 1⁄2"	80 55⁄64"	147 1⁄2"	144"	195 1⁄2"	120"
PXX - XXP	109 3⁄4"	80 55⁄64"	285 3⁄4"	144"	381 3⁄4"	120"
PXXX - XXXP	160"	80 55⁄64"	424"	144"	NA	NA
PXXXX - XXXXP	210 1⁄4"	80 55⁄64"	562 1⁄4"	144"	NA	NA
PXXXXX - XXXXXP	260 1⁄2"	80 55⁄64"	700 1⁄2"	144"	NA	NA

P = Pocket Panel X = Operating Panel

For the most complete technical information, visit marvin.com or talk with your Modern dealer.

MODERN DESIGN OPTIONS.
LIMITLESS POSSIBILITIES.



DIVIDED LITES

Achieve a unique aesthetic with divided lites on any Modern window or door. Select from a variety of customizable patterns, available on both dual pane and triple pane products.

Pictured right: Exterior detail of Simulated Divided Lites in Ebony

Pictured below: Modern Inswing door



SIMULATED DIVIDED LITES (SDL)

Aluminum interior + exterior

7/8" or 1 1/8" width

SIMULATED FRAME

Aluminum interior, high density fiberglass exterior

2 7/8" width




SILL OPTIONS

We’ve innovated every aspect of the new Modern line, right down to the smallest details. We offer flush sill options for both temperate and inclement conditions as well as a performance sill for areas where recessing isn’t an option.

Modern door sills are engineered with our proprietary High Density Fiberglass for superior strength and thermal performance. Available in Ebony or Bronze with aluminum liners and covers.


Pictured right: Detail of the Flush Sill

MULTI-SLIDE DOOR SILL OPTIONS



FLUSH SILL

- Recommended for protected areas
- Not certified for performance
- ADA compatible when properly installed



PERFORMANCE SILL

- Recommended for areas where performance is needed and the sill is not recessed
- Rated and certified for performance



HIGH PERFORMANCE SILL

- Rated and certified for superior performance
- ADA compatible when properly installed

SWINGING DOOR SILL OPTIONS



SADDLE SILL

- Not certified for performance
- ADA compatible when properly installed
- Available in dark bronze in thermally broken aluminum



LOW-PROFILE SILL

- Rated and certified for performance
- ADA compatible when recessed



PERFORMANCE SILL

- Rated and certified for performance
- Not ADA compatible



CURATED COLORS

Our intentionally selected color palette evokes the elemental nature of modern design. Choose split interior and exterior color finishes or matching finishes designed to coordinate.





HARDWARE FINISHES

From low-profile handles to nested locks, our hardware is designed to complement clean, modern lines while delivering reliable performance. Select from a variety of finishes and styles to fit your vision.

Pictured above: Casement and Awning Crank Out hardware and Multi-Slide door interior and exterior multi-point lock system handles

SCREENS

All screens are intentionally designed for uninterrupted views, ease of use, and a sleek modern look.

Pictured right: Modern Awning window
Pictured below: Modern Casement Crank Out window



CASEMENT AND AWNING PUSH OUT

- Concealed screen frame does not disrupt sightlines or view
- High transparency mesh
- Innovative latch color matched to the interior
- Concealed hinges support operability

CASEMENT AND AWNING CRANK OUT

- Concealed screen frame does not disrupt sightlines or view
- High transparency mesh
- Innovative latch color matched to the interior
- Crank in and out operability





THIS IS ONLY THE BEGINNING.

EXPERIENCE IT AT

YOUR MODERN DEALER TODAY.



At Marvin, we're driven to imagine and create better ways of living by designing windows and doors that open new possibilities for the people who use them.

To learn more visit us at **MARVIN.COM/MODERN**

19983042

Marvin Lumber and Cedar Co., Warroad, MN 56763.

©2021 Marvin Lumber and Cedar Co., LLC. All rights reserved.

®Registered trademark of Marvin Lumber and Cedar Co., LLC.

Information regarding status of patent applications, as well as product features and specifications, is subject to change without notice. August 2021.

For warranty information, please visit marvin.com

Please note: Colors shown in printed materials are simulations and may not precisely duplicate product or finish colors. Contact your local Modern dealer to view actual product and finish color samples.