




FINISHES: US3, US3A, US4, US5, US10B, US14, US15, US26

BEADED

508BD50


WILL NOT FIT 2 1/8" BORE.





PA/PR **\$244** SD **\$120**

508BD67






PA/PR **\$244** SD **\$120**

MILLED

511ML50


WILL NOT FIT 2 1/8" BORE.





PA/PR **\$244** SD **\$120**

511ML67






PA/PR \$244 SD \$120

EDGED

513ED50


WILL NOT FIT 2 1/8" BORE.





PA/PR \$244 SD \$120

513ED67





PA/PR \$244 SD \$120



FINISHES: US3, US3A, US4, US5, US10B, US14, US15, US26













OMNIA ARC

How to Order

Pesign 751

Rose Option

BD = Beaded

ED = Edged

5050 = 50 mm

Rose Size

 $67 = 67 \, mm$

238 = 2 ³/₈" Backset 234 = 2 ³/₄" Backset

0 = Single Dummy

Latch

F = "T" Strike F = Full Lip Strike

Strike

• PA
See Function
Codes Below*

Function

Finish

See Finish Codes Below**

ML = Milled

Example product order number would be 751ED50/238F.PA15

Product Data

Knob and Lever Latchset

- 2 3/8" (standard) and 2 3/4" backsets available.
- Supplied for 1³/₈" door thickness as standard.
 The minimum door thickness is 1 ¹/₄"; the maximum door thickness is 2 ¹/₂" (please specify).
- All lever latchsets meet ADA accessibility requirements.

Each set consists of solid brass knobs or levers, concealed screw finished roses, metal thrubolting spring-assisted rose cassette, latch, strike, dust box, faceplate, spindle, all necessary mounting screws, installation template and instructions.



Latchsets with any of the smaller roses are available with a pushbutton privacy function just like the larger roses.

About Our Tubular Latch

- 28° rotation to retract latch.
- Tough, non-rusting materials used throughout. Face covers and strikes are solid brass. No.013 "T" strike supplied as standard or No.014 "Full Lip" strike as an option. (Please specify.)
- Critical interior parts are made of solid brass.
- For over five decades, OMNIA's latches have been opening and closing millions of doors all around the world.

Function Codes*

O - Washer Installation Tool

Q - Emergency Release Key

P - Privacy Locking Pin (For Privacy ONLY)

- PA = Passage: Latch operates by knob or lever from either side of door.
- PR = Privacy: Push pin provided for privacy inside room. Emergency release hole for outside room. Emergency release key also provided.
- **SD = Single Dummy**: Trim on one side of door only. Concealed screw roses for surface mounting. Knob or lever with rose.

FINISH CODES**



3 Polished Brass, Lacquered



3APolished
Brass,
Unlacquered



US4Satin
Brass,
Lacquered



5Antique
Brass,
Lacquered



10BOil-Rubbed
Bronze,
Lacquered



14Polished
Nickel Plated,
Lacquered



15 Satin Nickel Plated, Lacquered



26 Polished Chrome

SMALL ROSES WILL NOT FIT 2 1/8" BORE.

ALL ROSES ARE CONCEALED SCREW MOUNTED.

Latchset Component List

- A Door Knob/Lever (2)
- B Set Screw (2)
- C Nylon Threaded Washer (2)
- D Finished Rose (2)
- Ea Metal Spring Assist Sub-Rose
- Eb Metal Spring Assist Sub-Rose
- F Spindle (Teardrop groove positioned towards set screw)
- G Tubular Latch
- H Privacy Locking Block Machine Screw
- I Privacy Locking Block Locking Stopper
- J Privacy Locking Block
- K Tubular Latch Faceplate
- L Tubular Latch Strike Plate
- M Tubular Latch Dust Box



N - Thru-Bolt Machine Screws With Locking Washer (2)

ENNIAINDUSTRIES, INC.

5 Cliffside Drive • Box 330 • Cedar Grove, New Jersey 07009 tel 973.239.7272 / fax 973.239.5960

www.OMNIAindustries.com







© Copyright 2018 OMNIA Industries, Inc. No. ARC0718